



MODEL  
**50-93/30-95**

GRAVITY FED  
COAL BURNING STOVE

**KEEPING YOU WARM**  
*for more than 30 years*



**EZ FLO**  
COAL



**MAINTENANCE-FREE:**

There are no moving parts in the E-Z Flo™ feed system. It requires no electricity to burn. This keeps the unit burning even in the event of a power outage. It uses anthracite nut or pea size coal, which is gravity-fed directly into the fire. Heavy cast iron shaker grates and a removable ash pan makes for easy ash removal.

**SAVINGS:**

Coal is one of the cheapest, most abundant fuels on the planet. The clean-burning anthracite coal, for which the Hitzer E-Z Flo™ is designed, helps save the planet's environment too. Anthracite coal is rich in clean-burning carbon but low in pollution-causing sulfur, dust and ash. "Nut" or "pea" sized coal is readily available in clean, easy-to-store 40 lb. bags. Anthracite produces more heat per dollar than virtually any other fuel.

**WARMTH:**

Anthracite coal burns hot but slow, radiating smooth, even warmth to every corner. Comfort that you can control with Hitzer's unique bi-metal thermostat. It has hours of heat stored up in the hopper. The optional distribution blower is great for circulating the heat to every area of the house.

**BEAUTY:**

The Swiss Amish craftsmanship of the E-Z Flo™ stoves adds charm to any decor, and the warm glow in the full-view window is a peaceful treat for the eyes and mind. Choose from black, forest green, metallic blue, charcoal, or honey-glo brown to compliment your room's color scheme. We offer only a few options • a gold plated door or pewter plated door • gold or pewter accents (handles and knobs).



*In Swiss, Hitzer means "heater". More importantly, Hitzer has come to mean quality, comfort, efficiency, value... and a commitment backed by superior Amish craftsmanship that provides you with years of heating performance.*



GOLD



PEWTER



50-93

	Width	Depth	Height
Unit	30"	21"	34 1/2"
Firepot	24 1/4"	14 1/2"	13 1/2"
Door Opening	19"	-	10 1/2"
Glass	17 7/16"	-	9"
Hopper Opening - 10" x 6"	Flue Size - 6" Diameter		

Unit to Sidewall: 20" • Unit to Backwall: 28" • Flue to Sidewall: 32" • Flue to Backwall: 18"

Automatic Draft Control



Optional 210 CFM Blower

**BTU Output:** 16,000-100,000  
**Hopper Capacity:** 50 lb. Anthracite Coal, Nut/Pea size.  
*(Hopper can be removed to burn stove-size anthracite or bituminous coal)*  
**1 lb. per hour – 7 lb. per hour**  
**Up to 2500 sq ft heating capacity**

1/4" Steel Top

Grate Shaker

Brass or Pewter Handles & Trim

ROBAX Glass

3/16" Steel Plate Construction

Cast Iron Doors  
 (Optional Gold or Pewter Plating)

Cast Iron Shaker Grate

Tested to UL Standard 1482

30-95

	Width	Depth	Height
Unit	24 1/2"	19 1/2"	34"
Firepot	20"	12"	18 1/2"
Door Opening	17"	-	10 1/2"
Glass	15 9/16"	-	9"
Hopper Opening - 14" x 6 1/2"	Flue Size - 6" Diameter		

Unit to Sidewall: 19" • Unit to Backwall: 27" • Flue to Sidewall: 28" • Flue to Backwall: 18"

Automatic Draft Control



Optional 134 CFM Blower

**BTU Output:** 11,000 – 65,000  
**Hopper Capacity:** 30 lb. Anthracite Coal, Nut/Pea size.  
*(Hopper can be removed to burn stove-size anthracite or bituminous coal)*  
**1 lb per hour – 4 lb. per hour**  
**Up to 1800 sq ft heating capacity**

1/4" Steel Top

Grate Shaker

Brass or Pewter Handles & Trim

ROBAX Glass

3/16" Steel Plate Construction

Cast Iron Doors  
 (Optional Gold or Pewter Plating)

Cast Iron Shaker Grate

Tested to UL Standard 1482

**Floor Protection:** Floor protector equal to 3/8" non-combustible millboard or equivalent, extending 18" in front, 8" each side and 12" to rear.

YOUR HITZER DEALER



Hitzer Inc.  
 269 East Main Street • Berne, IN 46711  
 (p) 260-589-8536 • (f) 260-589-3538  
 www.hitzer.com • info@hitzer.com

